

Specification


Cell Capacity : 3.7V/13000mAh
 Output Voltage : DC 5.1V
 Input Voltage : DC 5.0V
 Output Current: 2.0A/1.0A
 Input Current: 2.0A
 Size: 4.87" x 3.05" x 0.87" inch
 Weight: 11.11 OZ
 Operating Temperature: 0°C - 45°C
 The battery will be fully charged in 8 hours(5V/2A adapter required)



Package Includes:

1. P130 External Battery
2. Manual
3. Micro USB Cable
4. Warranty Card

Charging



The LED indicator will show the battery level of the P130 as seen below:

Button (Y/N)	Capacity	LED1	LED2	LED3	LED4
Charging N	0-25%	ON	ON	ON	ON
	25-50%	ON	ON	ON	Flashing
	50-75%	ON	ON	ON	ON
	75-99%	ON	ON	ON	ON
Full Charge	ON	ON	ON	ON	

Discharging

The LED indicator will show the battery level of the P130 as seen below:

Button (Y/N)	Capacity	LED1	LED2	LED3	LED4
Discharging Y	75-99%	ON	ON	ON	ON
	50-75%	ON	ON	ON	OFF
	25-50%	ON	ON	OFF	OFF
	1%-25%	ON	OFF	OFF	OFF
0%	OFF	OFF	OFF	OFF	

Safety and Maintenance

- ◆ Do not expose to open flame or extreme temperatures.
- ◆ Do not attempt to short-circuit.



- ◆ Do not drop in water or use in high humidity.



- ◆ Stop using if you see any liquid leaking, overheating and other unexpected conditions.




- ◆ The recommended operating temperature is between 10°C-45°C.



- ◆ Please Recycle.



SCUD




P130 Instructions

SCUD USA, INC.
 WWW.SCUDGROUPUS.COM
 Email: market@scudgroup.com

How to Charge P130

1. Attach the micro USB cable to the P130's micro USB input port.
2. Insert the other end of the cable into either (a) an AC adapter (not included) connected to a wall socket or (b) an active computer USB port.
3. The LED indicator will light up when it is charging. Each flashing LED shows the current level of power in the battery (as shown in the charging chart). The LED display will shut off automatically when charging is completed.



How to Charge Devices with P130

1. Plug the USB cable into the P130's USB output port.
2. If your device has a micro USB connection, insert it directly into your device. For other connections, select the proper connector attachment, then insert into your device.
3. The P130 will start charging once both cable ends are connected.
4. The P130 will shut off automatically once your device has completed charging.

